

EPP-400

ESAB Precision Plasmarc™ Power Supply

The new EPP-400 Precision Plasmarc power supply features a wide operating range and a proven reliable design to provide the best range of capabilities with the durability needed for the most demanding applications.

Part of ESAB's new m3 plasma system, the EPP-400 can be used for both plasma marking and plasma cutting. For plasma marking, the EPP-400 can tightly control the current all the way down to 12 amps. And it can reach all the way to up 400 Amps at 100% duty cycle.

The EPP-400 features a highly efficient, high-power factor design that saves you money. Effective cutting or beveling of thick plate requires more power. Power is a product of amperage and voltage. The EPP-400 power supply is designed to provide a high operating voltage of 200 Volts at 400 Amps, allowing higher standoff and better arc performance, especially while beveling, where a high operating voltage is essential.

The advanced solid state design gives smooth, well regulated output current and is constructed for maintenance free operation in the most demanding environments. It features digital amperage and voltage meters, panel or remote current control, and "fan-on-demand" technology to reduce intake of dust, thereby extending maintenance intervals.

All ESAB plasma power supplies feature a 3 year warranty.



Wide Operating Range

- Allows cutting and marking with same system
- Current control as low as 12 Amps
- Maximum output 400 Amps

Performance Where It Counts

- High Output Voltage Capacity
- More power for thick plate or beveling
- Better arc performance
- Higher standoff capacity
- Rated for 100% duty cycle

Power Efficiency

- Efficient, high-power factor design
- Power factor of 91%
- Among the most efficient designs available
- Fan-on-demand technology

Precision Plasmarc[™] 400

Specifications

Input Voltage.....	460V, 60 Hz., 3-Phase 400V, 50 Hz., 3-Phase 575V, 60 Hz., 3-Phase
Input Current (at rated load)	120 amps, 460V, 3-Phase 138 amps, 400V, 3-Phase 96 amps, 575V, 3-Phase
Rated Output Current	400 amps, 100% duty
Output Current Range (Marking)	12 to 50 amps
Output Current Range (Cutting)	50 to 400 amps
Output Voltage	200VDC @ 400 amps
Output Circuit Voltage	427VDC
Power Factor (at rated load)	91.0%
Dimensions	42.75" high X 37.25" wide X 45" deep (1085.8mm X 946.1mm X 1143mm)
Shipping Weight	2062 lbs. (935.3 kg)

Ordering Information

EPP-400 400 Volt, 50 Hz. Input CE Version	0558005614
EPP-400 460 Volt, 60 Hz. Input	0558005615
EPP-400 575 Volt, 60 Hz. Input	0558005616

Specifications subject to change without notice.



**ESAB - Your Partner
in Welding and Cutting**



In U.S.A.
411 S. Ebenezer Rd
P.O.Box 100545
Florence, SC 29501-0545
Phone (843) 664-4394
Fax (843) 664-4403

In Canada
6010 Tomken Road
Mississauga, Ontario L5T 1X9
Phone (905) 670-0220
Fax (905) 670-4879

In Mexico
AVE. Diego Diaz de Berlanga No. 130
Col. Nogalar
San Nicolas de los Garza, N.L. 66480
Monterrey, Mexico
Phone 52-8-305-3700
Fax 52-8-350-5920

www.esabcutting.com